





# COVERDECK<sup>®</sup>

## SYSTEMS



Reverse side of CARPET Tile



**1-800-550-3325**

[WWW.COVERDECK.COM](http://WWW.COVERDECK.COM)

# CARPET TILE

### SPECIFICATIONS:

**ITEM NUMBER: 1100**

**DIMENSIONS: 12 1/8" X 12 1/8"**

**THICKNESS: 5/8"**

**TILE WEIGHT: 1.03 lbs.**

**COVERDECK SYSTEMS<sup>®</sup>** modular, elevated, self draining **CARPET TILES** are designed to be installed on numerous surfaces for both indoor and outdoor usage. This product protects and beautifies your deck giving it the warmth and comfort of carpet.



### COLOR SELECTIONS




SUN BROWN



OLIVE



ECLIPSE



AQUAMARINE




SUMMER SPICE



SEAWEED




SATURN GRAY



BLACK PEARL



WHEAT GERM




WALNUT HUSK



CLOVER



MIDNIGHT BLUE



# CARPET TILE

**COVERDECK SYSTEMS® CARPET TILES** are a modular carpet system designed for indoor or outdoor installation. The interlocking tray elevates the 34oz. un-backed needlepoint polypropylene carpet finish 5/8" above the sub surface allowing the tiles to drain freely.

The snap together design makes installation easy and fast, requiring no special tools or adhesives. Our unique expansion joints allow the tiles to expand and contract individually to help prevent buckling. **COVERDECK SYSTEMS®** patented **CARPET TILE** (US Patent # 5666772) helps prevent concrete deterioration by elevating the carpet which can retain salts found in acid rain.

The unique design of the **COVERDECK SYSTEMS® CARPET TILE** and its 304 supporting legs promote instant drainage. Water sweeps through the tiles taking with it any dirt, sand, etc from the surface providing a self cleaning action. This flow through design also helps keep the subsurface clean.

The **COVERDECK SYSTEMS® CARPET TILE** is mildew, mold and stain resistant and has been treated with UV stabilizers to reduce fading.

## SUB SURFACES:


**COVERDECK SYSTEMS® CARPET TILES** can be installed over any hard surface including existing decks. If you are planning on using **COVERDECK SYSTEMS CARPET TILES** over grass or sand, we recommend using our **TEMPFLOOR®** as a base. Installation on roof decks may require a **PROTECTION MAT** (product #2002).

## FEATURES:

- **Drains instantly**
- **Protects your sub floor**
- **Super Easy to SNAP together**
- **Uses no adhesive**
- **Mildew and Mold resistant**
- **Carpet breathes freely**
- **Helps prevent concrete deterioration**
- **Accepts up to 16,000 lbs of dead Load per square foot**

## APPLICATIONS:

- **Balconies**
- **Basements**
- **Laundry Rooms**
- **Roof Decks**
- **Bathrooms**
- **Pool and Spa areas**
- **Garage**
- **Patios, Decks and Docks**
- **Trade Show and Exhibit Floor**



## TRAY SPECIFICATIONS

- **SIZE:** 12 1/8" x 12 1/8" x 1/2"
- **LOADING:** 16, 000 lbs. dead load per sq. ft.
- **SUPPORT:** Surface supported by 304 oversized gusseted supports.
- **LOCKS:** 32 latch locks; 2 sides with 8 male parts; 2 sides with 8 female parts
- **WEIGHT:** .95 lbs
- **FLAMMABILITY:** meets UL94-HB standards
- **MATERIAL:** Polypropylene
- **SERVICE RANGE:** -30° to +170°
- **TENSILE STRENGTH** (psi) ASTM D638 5300
- **FLEXURAL MODULUS** (105 psi, 73° F) ASTM D790 1.6
- **TENSILE MODULUS** (105 psi) AST638 .82
- **THERMAL EXPANSION** (10-5 inches/inch/°C) 6.5
- **SPECIFIC GRAVITY** AST D792 .093
- **SPECIFIC VOLUME**, In 3/lb. 30.5
- **ELECTRICAL SPECIFICATIONS**
  - ARC RESISTANCE, SEC. ASTM D495..... 150
  - DIELECTRIC CONSTANT (1 M Hz).....2.5
  - DIELECTRIC STRENGTH (Volts/Mil)?.....660

\*\*Resistant to Weak Acids, Weak Alkalies; Strong Alkalies  
\*\*Fungus and Mildew Resistant

